

Palm Impact Wrench

1/2" YU-RH4002T & 3/8" YU-RH3002T



Twin Hammer Mechanism

Durable, less vibration, excellent balance and no reaction force.
Ultra short length **85mm** only.






"Double-Air-Intake" Motor

By increased air flow can largely deliver powerful output.




Patented Technology "Double-Air-Intake"

Reshape air motor construction to Double-Air-Intake and Double-Air-Exhaust, largely increase air intake and rapidly exhaust after work. Significantly improve rotor efficient to high peak.



Single-Air-Intake



Double-Air-Intake

Variable Speed Trigger

Ensure the Anvil working steadily, prevent bolts from damage.

Aluminum Housing

Aluminum housing gives the Hammer & Motor a very rugged & robust protection.

Low Sound Level

Hindden muffler can greatly decrease working noise.

► Application

Mainly aim for working in confined space and assembling production line. Freely workable in any tight spaces!!

Specification

Model No.	YU-RH4002T	YU-RH3002T
Hammer	Twin Hammer	
Square Drive	1/2"	3/8"
Bolt Capacity	1/2" (13 mm)	
Working Torque	332 FT-LB (450 N-m)	
Max. Torque	369 FT-LB (500 N-m)	
Nut Breakaway	740 FT-LB (1004 N-m)	664 FT-LB (900 N-m)
Free Speed	7,500 R.P.M.	7,500 R.P.M.
Air Consumption	3.4 CFM (25 scfm, 96 L/min.)	
Air Inlet	1/4"	
Air Pressure	90 PSI	
Air Hose	3/8" (10 mm)	
Overall Length	85 mm	88 mm
Net Weight	1.11kg	1.1 kg
Sound (unload)	91 dB(A)	91 dB(A)

Patent No. & Country

EP 3351723	LA ROATS RESERVE
30.17.18.39 10.45	
ZL 2017 1 0547151.2	
ZL 2017 3 0	029100.1
M541520,	D185042
D186584,	D223013
	ZL 2017 3 0 M541520,





Yueh-Chi Enterprise Co., Ltd.

www.scorpiotool.com.tw sales@scorpiotool.com.tw